




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup> :</b>  <b>G09G 3/02, G08C 21/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 91/06939</b>  <b>(43) International Publication Date:</b> <b>16 May 1991 (16.05.91)</b>
<b>(21) International Application Number:</b> PCT/US90/06242 <b>(22) International Filing Date:</b> 1 November 1990 (01.11.90)  <b>(30) Priority data:</b> 432,073                   6 November 1989 (06.11.89)   US  <b>(71) Applicant:</b> CALCOMP, INC. [US/US]; 2411 West La Palma Avenue, Post Office Box 3250, Mail Number 20, Anaheim, CA 92803 (US).  <b>(72) Inventors:</b> BEAUVAIS, Donald, Andrew ; 20235 North 3rd Drive, Apartment 2, Phoenix, AZ 85027 (US). SCHMENK, Steven, R. ; 9941 East Mission Lane, Scottsdale, AZ 85258 (US).		<b>(74) Agent:</b> IMAI, Keiichiro; 4500 Park Granada Boulevard, Calabasas, CA 91399 (US).  <b>(81) Designated States:</b> AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), NL (European patent), NO, SE (European patent).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** DIGITIZER TABLET SYSTEM WITH DUAL-MODE CURSOR/MOUSE**(57) Abstract**

This is a dual-mode digitizing tablet system for providing inputs to a user program. There is a tablet (20) with an active surface and an output connected to the computer. A cursor (18) is moveable over the surface for generating a first signal reflecting the position thereof. Two switch-activating buttons (14) on the cursor generate a second signal when pushed. A position history table (48) holds a last position of the cursor (18) and a menu definition table (52) holds entries defining menu selections associated with the user program (56) as a function of preestablished positions on the tablet. Dual-mode logic (46) is disposed between the tablet (20) and the user program (56) for determining and storing a present location of the cursor (18) for outputting the present location of the cursor when one of the buttons (14) is pressed, for otherwise outputting both the present location and relative movement of the cursor, and for outputting an indication when the other button is pressed. Finally there is an interfacing program (50) disposed between the dual-mode logic (46) and the user program (56) for receiving the present location of the cursor (18) when the one button (14) is pressed, for using the present location of the cursor (18) to retrieve an associated one of the menu selections from the menu definition table (52), and for providing the menu selection to the user program (56). Replaceable menu overlays for each user program are clipped to the tablet surface.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MR	Mauritania
BE	Belgium	GA	Gabon	MW	Malawi
BF	Burkina Faso	GB	United Kingdom	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CI	Côte d'Ivoire	LK	Sri Lanka	TD	Chad
CM	Cameroon	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

## DIGITIZER TABLET SYSTEM WITH DUAL-MODE CURSOR/MOUSE

5

### Background of the Invention:

This invention relates to digitizer systems for providing inputs to a computer and, more particularly, in a digitizing tablet system wherein the position on the surface of a tablet of a cursor device  
10 having at least two switch-activating buttons is sensed and signals reflecting the position of the cursor device and the pushing of the buttons are output to a computer connected thereto for use by a computer program running therein, to the improvement of the present invention to provide for user-controlled, dual-mode  
15 operation of the cursor device comprising, position history table means for holding at least a last position of the cursor device; and, dual-mode logic means disposed between the tablet and cursor device on one side and the computer program on another side for determining a present absolute location of the cursor device on the  
20 surface of the tablet and storing it in the position history table means, for supplying the computer program with the present absolute location of the cursor device on the surface of the tablet to indicate a menu selection location when a pre-selected one of the switch-activating buttons is pressed by a user, and for otherwise  
25 supplying the computer program with both the present absolute location of the cursor device on the surface of the tablet and an indication of relative movement of the cursor device across the surface of the tablet by the user being the difference between the present location of the cursor device on the surface of the tablet  
30 and a next previous location of the cursor device on the surface of the tablet from the position history table means whereby the user can selectively control the use of the cursor device as an absolute position device or as a relative movement device.

A primary object of most computer systems and the software  
35 packages operating thereon is to be "user friendly". In other words,

early computers could only be operated by persons trained in operating them. Accordingly, the number of computers available was few and they were mostly in business, military, and educational environments. With the advent of "personal computers", however, 5 virtually everyone has the potential of being impacted by computer availability. Even at the kindergarten and pre-school level, programs like LOGO allow even the youngest children to interface with the computer on a real-time basis and in a productive manner.

A major step in the attaining of user friendly status in various 10 popular computer systems has been the introduction of various input "pointing" devices. Discounting so-called "video games" and their "joy-sticks" as being outside of the dynamic actual computer interface under consideration, the first major input device to attain general use and popularity was the mouse. A typical prior art 15 mouse is shown in Figures 1-3 where it is generally indicated as 10. The mouse 10 has a body 12 which is easily gripped between a user's thumb and outer fingers to be slid across a surface (generally adjacent the keyboard of the computer). The body 12 has one or more switches (not shown) inside which can be activated by 20 pressing the buttons 14 on the top of the body 12 with the index or middle finger which extend along the top of the body 12 when the mouse 10 is in use. While there are optical mice (requiring a special surface for movement), the usual approach is to have a weighted rubber ball 16 inside of the body 12 which rolls on the 25 surface when the mouse 10 is slid over it. Sensing apparatus (not shown) inside of the body develops a pair of changing signals corresponding to longitudinal movement of the mouse 10 and transverse movement of the mouse 10 corresponding to movement in an orthogonal X-Y coordinate system lying in the plane of the 30 surface over which the mouse 10 is being moved. These signals and the closing of the switches by the pressing of the buttons 14 are transmitted to the computer (not shown) attached thereto by means of the connecting cable 16. Typically the cable 16 is connected to a serial input port of the computer since the data rate of transfer is

3

slow enough to allow use of the simpler and less costly serial approach as opposed to inputting on a parallel basis.

Most, if not all, of the word processing, spread sheet, and desktop publishing programs in common use today operate on a menu system. Typically, the user views the dynamic portions of the program on a monitor while providing inputs thereto from the computer's keyboard or by movement of a mouse (such as mouse 10). Changes in the function being performed are made through menu selection. Typically, the menu selections can be input through the keyboard if desired. It is easier and more "user friendly", however, to make the menu selections using the mouse and simply pointing to the desired option. In some cases, the menu selections are located at one or more of the edges of the monitor display. The mouse is simply moved across and up/down in a manner which makes a cursor appearing on the screen (which moves in combination with movement of the mouse 10) move to the desired menu selection. One of the buttons 14 is then pressed to make the computer (and program running therein) implement the menu selection just made.

Where the running program is complex and provides numerous menu options and sub-options, it is virtually impossible to locate the menu options around the display. In such cases, it is common to employ so-called "pull-down" menus. Only major menu headings are displayed on the monitor. To make a menu selection, the user moves the mouse 10 to the major menu heading containing the desired menu selection and presses one of the buttons 14. The computer then "pulls down" the entire menu associated with the selected heading across as much of the display as needed. The user then employs the mouse to make further selections -- which may include further pulling down of sub-menu portions. When the final menu selection of the chain has been made, the computer implements the selection and removes the menu portions from the display to allow further use of the display in its normal manner.

As will be realized and recognized from the foregoing description, the mouse 10 of Figures 1-3 operates in a relative

mode; that is, the computer program sensing the inputs from the mouse 10 recognizes only movement of the mouse 10 in the X and Y directions as it is slid over the surface upon which it is resting. If the mouse 10 is lifted and repositioned on the surface, no change in the signal to the computer will occur.

For some computer-based operations (most notably computer aided design (CAD) drawing digitizing), a method of indicating absolute position was necessary. For this purpose, digitizing tablet systems such as that shown in simplified form in Figures 4-7 were developed. A digitizing tablet system is comprised of two portions - a cursor device 18 (as depicted in Figures 4-6) and a tablet 20 (as depicted in Figure 7). The cursor device 18 can take the shape of a pen wherein the position of the tip thereof is sensed or can be a so-called "puck" as in the case of the cursor device 18 depicted in Figures 4-6. The puck type of cursor device is typically the more versatile. In a digitizing tablet system, the tablet 20 provides the surface over which the cursor device 18 is moved and there is an interaction between the two which permits the position of the cursor device 18 on the surface of the tablet 20 to be sensed. Thus, such systems operate in an absolute mode. When the mouse 10 was lifted and moved to another position on its supporting surface, its output signal did not change. By contrast, if the cursor device 18 is lifted and moved to a new position on the surface of the tablet 20, the signal output will change to reflect the new absolute position of the cursor device 18. Various ways are employed in the art to determine the position of the cursor device 18 on the surface of the tablet 20. One of the more common is electromagnetic field sensing. The cursor device 18 is connected to the tablet 20 by a connecting cable 22 and the tablet 20, in turn, is connected to the computer by a connecting cable 16 like the mouse 10. The tablet 20 has a grid of horizontal and vertical wires (not shown) therein extending over an active area 24. The cursor device 18 has a transparent frontpiece 26 containing a coil of wire 28 connected to the cable 22. Typically, several buttons 14 connected to switches (not shown) are also provided as in the case of the mouse 10 so that

5

the user can provide selection inputs to the computer. The frontpiece 26 has a set of crosshairs 30 formed therein at the electrical center of the coil of wire 28. If an alternating current signal is applied to the coil of wire 28, it will induce an electrical signal into the wires of the grid in the tablet 20 which can be sensed to provide and indication of the absolute location of the crosshairs 30 on the surface of the tablet 20. Alternatively, the wires of the grid can be "strobed" with a current signal which will induce a signal into the coil of wire 28. By knowing the timing of the strobed signal, the point in time when the signal is induced into the coil of wire 28 can be employed to provide and indication of the absolute location of the crosshairs 30 on the surface of the tablet 20. Thus, to input a drawing into a CAD system employing the digitizing tablet system of Figure 4-7, a user would tape the drawing over the active area 24 of the tablet 20, move the crosshairs 30 along the lines of the drawing to be digitized into the computer, and press one of the buttons 14 at each point to be digitized.

Once such digitizing tablet systems became available, their potential for other uses and as an improvement over the mouse soon became apparent to those skilled in the art. For example, when dynamically drawing with a CAD system employing a mouse and a menu system on the display, much time is lost working through the menu system to make desired selections. By replacing the mouse with the digitizing tablet system and some interfacing software, a user's throughput on a CAD system can be increased dramatically. The prior art approach to this solution is depicted in Figure 8. An overlay is placed on the surface of the tablet 20 covering some or all of the active area 28. There is a small working area 32 corresponding to the contents of the monitor display in which the actual "drawing" is done by the user. Surrounding the working area 32 is a menu grid 34 containing blocks 36 representing the various menu selections possible. The blocks 36 each contains an indicia (not shown) indicating what menu function is associated with the block. Prior to use, the menu grid 34 and its position must be identified to the using program by a setup routine. The user

employs the computer keyboard and the cursor device 18 to indicate the number of blocks 36 in various grid portions along with their corner locations and the corner locations of the working area. In use, the user moves the coil of wire 28 over the working area 32 to draw while watching the display on the monitor to see the results of the movement. To change functions, the crosshairs 30 are positioned on the block 36 associated with the new function and one of the buttons 14 is pressed to cause the computer to sense the position of the crosshairs 30, recognize the position as a particular menu function, and implement that function. The user then returns to drawing in the working area 32 with the new function.

As those skilled in the art will readily recognize and appreciate, the foregoing approach to using a digitizing tablet system with combined menu and working area designations within the active area could provide similar benefits to other menu-driven application programs such as desktop publishing, spread sheets, word processing, etc. Unfortunately, there are several factors working against such uses. The primary one is cost. A typical "small" digitizing tablet system retails for about \$500. Moreover, the same "small" tablet is about eighteen inches square -- not an insignificant footprint on the average user's desktop. Accordingly, the necessary interfacing software has not been written for such other applications. The only concession to the existence of such other applications in the overall working environment of persons and companies having digitizing tablet systems for use with CAD systems in the manner of Figure 8 is a mouse emulation program which allows the user to use his cursor device 18 on the tablet 20 in the manner of a mouse (i.e. the signal representing absolute position is used to calculate relative movement which is output to the using program) so that both a mouse and tablet system are not necessary and the user does not have to switch between them. Unfortunately, such emulation programs do not appear to work in a satisfactory emulation of a mouse and most users do use both devices and switch between them depending on which device the program being used expects as its input device.



Wherefore, it is an object of this invention to provide a digitizing tablet system which is of a size and price which can truly make it a "mouse substitute" device.

It is another object of this invention to provide a digitizing  
5 tablet system which operates in a dual mode indicating either relative movement or absolute position under the control of the user.

Other objects and benefits of the invention will become apparent from the detailed description which follows hereinafter  
10 when taken in conjunction with the drawing figures which accompany it.

#### Summary:

The foregoing objects have been attained by the dual-mode  
15 digitizing tablet system of the present invention for providing inputs to a user program running in a computer to allow a user to control the operation of the user program comprising, a tablet having an active surface portion and an output connected to the computer; sensible cursor device means connected to the tablet and moveable  
20 over the active surface for generating a first signal at the output of the tablet reflecting the position on the active surface of the cursor device means, the cursor device means having at least two switch-activating buttons and including means for generating a second signal at the output of the tablet reflecting the pushing of the  
25 buttons by a user; position history table means for holding at least a last position of the cursor device means; menu definition table means disposed in the computer and holding a plurality of entries for defining menu selections associated with the user program as a function of pre-established positions on the active surface of the  
30 tablet; dual-mode logic means disposed between the tablet and cursor device means on one side and the user program on another side for determining a present absolute location of the cursor device means on the active surface of the tablet and storing it in the position history table means, for outputting the present absolute  
35 location of the cursor device means on the active surface of the

tablet to indicate a menu selection location when a pre-selected one of the switch-activating buttons is pressed by a user, for otherwise outputting both the present absolute location of the cursor device means on the active surface of the tablet and an indication of relative movement of the cursor device means across the active surface of the tablet by the user being the difference between the present location of the cursor device means on the active surface of the tablet and a next previous location of the cursor device means on the active surface of the tablet from the position history table means, and for outputting an indication when other than the pre-selected one of the switch-activating buttons is pressed by the user; and, interfacing program means disposed in the computer between the dual-mode logic means and the user program for receiving the present absolute location of the cursor device means on the active surface of the tablet when the pre-selected one of the switch-activating buttons is pressed by a user, for using the present absolute location of the cursor device means on the active surface of the tablet to retrieve an associated one of the menu selections for the location from the menu definition table means, and for providing the associated one of the menu selections to the user program whereby the user can selectively control the use of the cursor device means as an absolute position device or as a relative movement device.

In the preferred embodiment, the interfacing program means includes means for determining if the user program expects data from an absolute device or a relative device and for providing the appropriate one to the user program from the present absolute location of the cursor device means on the active surface of the tablet and the indication of relative movement of the cursor device means across the active surface of the tablet by the user as received from the dual-mode logic means. Also, there are menu overlay means positioned on the active surface of the tablet and containing a plurality of indicia thereon for associating the pre-established positions on the active surface of the tablet with the menu selections associated with the user program as a function of the pre-

established positions as contained in the menu definition table means as well as clip means on the active surface of the tablet for positioning and holding the menu overlay means in a pre-established position on the active surface of the tablet with the  
5 indicia disposed over respective ones of associated the pre-established positions on the active surface of the tablet.

Description of the Drawings:

Figure 1 is a simplified side view of a prior art mouse type  
10 input device.

Figure 2 is a simplified front view of the mouse type input device of Figure 1.

Figure 3 is a simplified top view of the mouse type input device of Figures 1 and 2.

15 Figure 4 is a simplified top view of a prior art puck type input device as employed with a digitizer tablet.

Figure 5 is a simplified front view of the puck type input device of Figure 4.

20 Figure 6 is a simplified side view of the puck type input device of Figures 4 and 5.

Figure 7 is a simplified plan view of a prior art digitizer tablet as employed with the puck type input device of Figures 4-6.

25 Figure 8 is a simplified plan view of the digitizer tablet of Figure 7 showing the prior art method of using the tablet when employing a menu therewith.

Figure 9 is a simplified top view of a preferred dual mode cursor/mouse type input device as employed in the system of the present invention.

30 Figure 10 is a simplified front view of the cursor/mouse type input device of Figure 9.

Figure 11 is a simplified top view of the cursor/mouse type input device of Figures 9 and 10.

Figures 12 and 13 are simplified plan views of a prior art digitizer tablet such as that of Figure 7 showing the approach of the

present invention for using the tablet when employing a menu therewith.

Figure 14 is a drawing of the tablet employed in the preferred embodiment of the present invention depicting the way it is employed when it is being employed by a user to make a menu selection.

Figure 15 is a drawing of the tablet employed in the preferred embodiment of the present invention depicting the way it is employed when it is not being employed by a user to make a menu selection.

#### Description of the Preferred Embodiment:

The elements of a dual-mode cursor/mouse digitizing tablet system as will soon be sold commercially by the assignee of this application under the trademark WIZ are depicted in Figures 9-15. There is a cursor/mouse cursor device 18' (Figures 9-11) and a tablet 20' (Figures 12-13). The actual sensing system employed is conventional and, therefore, will not be addressed herein. The major point of novelty is the system as a whole, as depicted in functional block diagram form in Figure 14, and the logic employed therein, as depicted in the logic flowchart of Figure 15.

The cursor device 18' is of a unique design intended to give the typical mouse user the familiar feel of a mouse and is the subject of co-pending application serial no. \_\_\_\_\_ entitled DIGITIZER CURSOR/MOUSE WITH UNITARY SWITCH ACTUATORS by Lynn H. Rockwell, which is assigned to the common assignee of this application and being filed on even date herewith. While the cursor device 18' provides the feel of a mouse to a user, it still possesses a transparent frontpiece 26 carrying the coil of wire 28 used for position sensing as well as the crosshairs 30 for positioning the coil of wire 28 over a menu selection as will be described shortly.

The tablet 20' is of generally conventional design; but, to eliminate the setup requirements of the prior art approach of Figure 8 and provide flexibility and interchangeability, it has menu

retaining and alignment clips <sup>11</sup>38 provided in the top surface 40 adjacent the edges of the active area 24 as best seen with reference to Figure 12. The tablet 20' of the commercial WIZ system will be about the size of a standard writing tablet (i.e. about nine by twelve inches) with the active area 24 being about nine inches square. This small size (and attendant small footprint and small selling price) was made possible by unique manufacturing techniques implemented by the assignee hereof in order to make the WIZ system meet its stated objective of being a practical replacement for a mouse for the common (i.e. non-commercial) user. As depicted in Figure 12, the clips 38 hold a selected rectangular plastic menu overlay 42 corresponding to the program in use in an exact and reproducible position on the active area 24. Each menu overlay 42 has menu selections 44 printed thereon for its associated program. Thus, the interfacing selection logic can be pre-programmed at the factory as to the absolute positions of the menu selections 44 and, therefore, no setup by the user is required, ever. Note also that there is no "working area" associated with the menu overlay 42. This is because of the unique dual-mode approach of the present invention.

As will be realized from an in-depth review of the above-referenced, co-pending Rockwell application, the three buttons 14' at the front of the cursor device 18' are, in fact, bi-directional actuators each connected to two microswitches. By depressing the front edge of a button 14', one switch is actuated while by depressing the back edge of the same button 14', a second switch is actuated. Thus, the cursor/mouse cursor device 18' in its preferred embodiment has six switches that can be activated by a user. One of the switches is associated with a MENU SELECT function. Hereinafter and in the claims that follow, when the "MENU SELECT button" is referred to, it means that button 14' which closes the switch associated with a MENU SELECT function when it is pushed.

As depicted in Figure 14, the signals out of the tablet 20' on connecting cable 16 are provided to the remainder of the system

comprising dual-mode logic <sup>12</sup>46, position history memory 46, interfacing program 50, and menu definitions 52 contained within the computer 54. While dual-mode logic 46 and interfacing program 50 are depicted for convenience and ease of understanding as separate entities, in an actual implementation they would probably be combined together. Similarly, in the preferred implementation the dual-mode logic 46 and interfacing program 50 would most likely be implemented as computer software. Those skilled in the art will readily recognize and appreciate that the implementation of the dual-mode logic 46 and interfacing program 50 could be done in other ways well known in the art within the scope and spirit of this invention. The programming approach is preferred only because of its simplicity and low cost which aid in obtaining the objectives of the invention.

As can be seen from Figure 14, the dual-mode logic 46 and interfacing program 50 are positioned between the tablet 20' (with cursor device 18') providing the user's inputs and the user programs 56 within the computer 54 operating and being controlled by the user. The menu definitions 52 are pre-established and relate absolute locations on the active area 24 of the tablet 20' with menu selections 44 on various overlays 42 with their corresponding menu selections within the associated user program 56. Thus, if the user is running a user program 56 called "WRITE", an overlay 42 for the WRITE program is placed in the clips 38 to properly and accurately align it on the active area 24 of the tablet 20'. The user then makes menu selections within the WRITE program by positioning the crosshairs 30 of the cursor device 18' over that menu selection 44 on the overlay 42 and presses the MENU SELECT button 14'. The interfacing program 50 then looks up the location of the cursor device 18' when the MENU SELECT button 14' was pushed in the menu definitions 52 in that portion containing the pre-established definitions for the program WRITE. Associated with the location in the menu definitions 52 is the corresponding menu selection, which is then passed on to the user program WRITE. This overall approach is accomplished as follows.

Signals from the cursor <sup>13</sup>18' and tablet 20' representing the present position of the cursor 18' (i.e. the sensed coil of wire 28) as well as the pushing of any of the buttons 14' by the user are input from the tablet 20' to the computer 54 (and dual-mode logic 46) over the connecting cable 16 mentioned earlier. As depicted in Figure 15, the logic 46 inputs the X and Y (i.e. absolute) position of the cursor device 18' and saves it in the position history memory 48. It then checks to see if the "MENU SELECT" button 14' has been pressed by the user. If it has, the user is using the cursor device 18' in its absolute mode to indicate a menu selection. In such case, the logic 46 passes the menu selection location to the interfacing program 50. The interfacing program 50 uses the location to access the pre-established menu definitions contained in the menu definitions 52 for the user program 56 which is presently operating in the manner described above. If the "MENU SELECT" button 14' has not been pressed by the user, the cursor device 18' is not being operated in the absolute mode to make a menu selection. In such case, it may be operating in either a relative mode (i.e. as a mouse as in the case of a word processing program, for example) or in an absolute mode (i.e. as a digitizing cursor as in the case of a CAD program, for example). The logic 46 checks to see if any of the other buttons 14' have been pressed by the user and, if one has, the particular button 14' (i.e. the switch associated therewith) is identified to the interfacing program 50. In either case, the logic 46 then passes on both the present absolute location of the cursor device 18' and its relative movement since the last update to the interfacing program 50. The interfacing program 50 then passes either the position or the movement to the user program 56 presently operating, as appropriate. This knowledge is pre-programmed into the interfacing program 50 at the same time as the menu definitions 52 and, if desired, can be provided as part of the menu definitions information to accessed in tabular form by a general purpose interfacing program. In such case, to add additional user programs 56, only additional data to the menu definitions 52 would have to be provided.

Thus, it can be seen from the foregoing description that the  
present invention has truly met its stated objective by providing a  
mouse substitute digitizing tablet device which can provide all the  
benefits of a selectable menu digitizing tablet with the flexibility and  
5 feel of a mouse -- all at a low cost and small size which can put the  
benefits thereof virtually in the hands of any user.

Wherefore, having thus described our invention, what is  
claimed is:



15

1. In a digitizing tablet system wherein the position on the surface of a tablet of a cursor device having at least two switch-activating buttons is sensed and signals reflecting the position of the cursor device and the pushing of the buttons are output to a computer connected thereto for use by a computer program running therein, the improvement to provide for user-controlled, dual-mode operation of the cursor device comprising:
- a) position history table means for holding at least a last position of the cursor device; and,
  - b) dual-mode logic means disposed between the tablet and cursor device on one side and the computer program on another side for determining a present absolute location of the cursor device on the surface of the tablet and storing it in said position history table means, for supplying the computer program with said present absolute location of the cursor device on the surface of the tablet to indicate a menu selection location when a pre-selected one of the switch-activating buttons is pressed by a user, and for otherwise supplying the computer program with both said present absolute location of the cursor device on the surface of the tablet and an indication of relative movement of the cursor device across the surface of the tablet by the user being the difference between said present location of the cursor device on the surface of the tablet and a next previous location of the cursor device on the surface of the tablet from said position history table means whereby the user can selectively control the use of the cursor device as an absolute position device or as a relative movement device.

2. The improvement to a digitizing tablet system of claim 1 and additionally comprising:

said dual-mode logic means including logic for indicating to the computer program when other than said pre-selected one of the switch-activating buttons is pressed by a user.

16

3. The improvement to a digitizing tablet system of claim 1 wherein the computer program includes at least one user program and additionally comprising:

5 a) menu definition table means disposed in the computer and holding a plurality of entries for defining menu selections associated with said user program as a function of pre-established positions on the surface of the tablet; and,

10 b) interfacing program means disposed in the computer between said dual-mode logic means and said user program for receiving said present absolute location of the cursor device on the surface of the tablet when said pre-selected one of the switch-activating buttons is pressed by a user, for using said present absolute location of the cursor device on the surface of the tablet to retrieve an associated one of said menu selections for said  
15 location from said menu definition table means, and for providing said associated one of said menu selections to said user program.

4. The improvement to a digitizing tablet system of claim 3 and additionally comprising:

20 menu overlay means positioned on the surface of the tablet and containing a plurality of indicia thereon for associating said pre-established positions on the surface of the tablet with said menu selections associated with said user program as a function of said pre-established positions as contained in said menu definition  
25 table means.

5. The improvement to a digitizing tablet system of claim 4 and additionally comprising:

30 clip means on the surface of the tablet for positioning and holding said menu overlay means in a pre-established position on the surface of the tablet with said indicia disposed over respective ones of associated said pre-established positions on the surface of the tablet.

6. In a digitizing tablet system wherein the position on the surface of a tablet of a cursor device having at least two switch-activating buttons is sensed and signals reflecting the position of the cursor device and the pushing of the buttons are output to a computer connected thereto for use by a user computer program running therein, the improvement to provide for user-controlled, dual-mode operation of the cursor device to control operation of the user computer program comprising:
- a) position history table means for holding at least a last position of the cursor device;
  - b) menu definition table means disposed in the computer and holding a plurality of entries for defining menu selections associated with said user computer program as a function of pre-established positions on the surface of the tablet;
  - c) dual-mode logic means disposed between the tablet and cursor device on one side and the user computer program on another side for determining a present absolute location of the cursor device on the surface of the tablet and storing it in said position history table means, for outputting said present absolute location of the cursor device on the surface of the tablet to indicate a menu selection location when a pre-selected one of the switch-activating buttons is pressed by a user, for otherwise outputting both said present absolute location of the cursor device on the surface of the tablet and an indication of relative movement of the cursor device across the surface of the tablet by the user being the difference between said present location of the cursor device on the surface of the tablet and a next previous location of the cursor device on the surface of the tablet from said position history table means, and for outputting an indication when other than said pre-selected one of the switch-activating buttons is pressed by a user; and,
  - d) interfacing program means disposed in the computer between said dual-mode logic means and said user computer program for receiving said present absolute location of the cursor device on the surface of the tablet when said pre-

18

selected one of the switch-activating buttons is pressed by a user, for using said present absolute location of the cursor device on the surface of the tablet to retrieve an associated one of said menu selections for said location from said menu definition table means, and for providing said associated one of said menu selections to said user program whereby the user can selectively control the use of the cursor device as an absolute position device or as a relative movement device.

7. The improvement to a digitizing tablet system of claim 6 wherein:

said interfacing program means includes means for determining if said user computer program expects data from an absolute device or a relative device and for providing the appropriate one to said user computer program from said present absolute location of the cursor device on the surface of the tablet and said indication of relative movement of the cursor device across the surface of the tablet by the user as received from said dual-mode logic means.

8. The improvement to a digitizing tablet system of claim 6 and additionally comprising:

menu overlay means positioned on the surface of the tablet and containing a plurality of indicia thereon for associating said pre-established positions on the surface of the tablet with said menu selections associated with said user computer program as a function of said pre-established positions as contained in said menu definition table means.

9. The improvement to a digitizing tablet system of claim 8 and additionally comprising:

clip means on the surface of the tablet for positioning and holding said menu overlay means in a pre-established position on the surface of the tablet with said indicia disposed over

respective ones of associated said pre-established positions on the surface of the tablet.

10. A dual-mode digitizing tablet system for providing  
5 inputs to a user program running in a computer to allow a user to control the operation of the user program comprising:
- a) a tablet having an active surface portion and an output connected to the computer;
  - b) sensible cursor device means connected to said  
10 tablet and moveable over said active surface for generating a first signal at said output of said tablet reflecting the position on said active surface of said cursor device means, said cursor device means having at least two switch-activating buttons and including means for generating a second signal at said output of said tablet reflecting  
15 the pushing of said buttons by a user;
  - c) position history table means for holding at least a last position of said cursor device means;
  - d) menu definition table means disposed in the computer and holding a plurality of entries for defining menu  
20 selections associated with the user program as a function of pre-established positions on said active surface of said tablet;
  - e) dual-mode logic means disposed between said tablet and cursor device means on one side and the user program on another side for determining a present absolute location of said  
25 cursor device means on said active surface of said tablet and storing it in said position history table means, for outputting said present absolute location of said cursor device means on said active surface of said tablet to indicate a menu selection location when a pre-selected one of said switch-activating buttons is pressed by a user,  
30 for otherwise outputting both said present absolute location of said cursor device means on said active surface of said tablet and an indication of relative movement of said cursor device means across said active surface of said tablet by the user being the difference between said present location of said cursor device means on said  
35 active surface of said tablet and a next previous location of said

20

cursor device means on said active surface of said tablet from said position history table means, and for outputting an indication when other than said pre-selected one of said switch-activating buttons is pressed by the user; and,

- 5           d) interfacing program means disposed in the computer between said dual-mode logic means and the user program for receiving said present absolute location of said cursor device means on said active surface of said tablet when said pre-selected one of said switch-activating buttons is pressed by a user,  
10 for using said present absolute location of said cursor device means on said active surface of said tablet to retrieve an associated one of said menu selections for said location from said menu definition table means, and for providing said associated one of said menu selections to the user program whereby the user can selectively  
15 control the use of said cursor device means as an absolute position device or as a relative movement device.

11. The dual-mode digitizing tablet system of claim 10 wherein:

- 20           said interfacing program means includes means for determining if the user program expects data from an absolute device or a relative device and for providing the appropriate one to the user program from said present absolute location of said cursor device means on said active surface of said tablet and said  
25 indication of relative movement of said cursor device means across said active surface of said tablet by the user as received from said dual-mode logic means.

12. The dual-mode digitizing tablet system of claim 10 and  
30 additionally comprising:

          menu overlay means positioned on said active surface of said tablet and containing a plurality of indicia thereon for associating said pre-established positions on said active surface of said tablet with said menu selections associated with the user

21

program as a function of said pre-established positions as contained in said menu definition table means.

13. The dual-mode digitizing tablet system of claim 12 and  
5 additionally comprising:

clip means on said active surface of said tablet for  
positioning and holding said menu overlay means in a pre-  
established position on said active surface of said tablet with said  
indicia disposed over respective ones of associated said pre-  
10 established positions on said active surface of said tablet.




FIG. 1






FIG. 2




PRIOR ART

FIG. 3




PRIOR ART

FIG. 4




PRIOR ART

FIG. 5




PRIOR ART

FIG. 6



PRIOR ART

FIG. 7



PRIOR ART

FIG. 8









FIG. 12






FIG. 13



# INTERNATIONAL SEARCH REPORT

International Application No **PCT/US90/06242**

## I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) <sup>2</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC(5): G09G 3/02, G08G 21/00

U.S. CL.: 178/18; 340/706

## II. FIELDS SEARCHED

Minimum Documentation Searched <sup>4</sup>

Classification System <sup>1</sup>

Classification Symbols

U.S. 178/18, 19; 340/706, 710, 712, 734

Documentation Searched other than Minimum Documentation  
to the Extent that such Documents are Included in the Fields Searched <sup>5</sup>

## III. DOCUMENTS CONSIDERED TO BE RELEVANT <sup>14</sup>

Category <sup>6</sup>	Citation of Document, <sup>16</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>
-----------------------	--	-------------------------------------

Y,P	US, A, 4,954,817 (LEVINE) 04 September 1990, See the entire document.	1-13
Y	US, A, 4,677,258 (KAWASHIMA) 30 June 1987, See the entire document.	1-13
Y	US, A, 4,654,648 (HERRINGTON) 31 March 1987, See Fig. 5; col. 4, lines 36-46; and Col. 10, lines 47-55.	1-13
Y	US, A, 4,578,768 (RACINE) 25 March 1986, See Fig. 3; and Col. 5, lines 7-14.	4-5,8,9,12,13

### \* Special categories of cited documents: <sup>15</sup>

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search <sup>3</sup>

27 NOVEMBER 1990

Date of Mailing of this International Search Report <sup>3</sup>

25 FEB 1991

International Searching Authority <sup>1</sup>

ISA/US

Signature of Authorized Officer <sup>20</sup>

MATTHEW LOU